



WS WALL SOCKET

ELECTRICAL

Rated Voltage	250V a.c.
Rated Current	13Amp
Frequency	50Hz
Terminal capacity: Live, Neutral & Earth	2 x 2.5 mm ²

ENVIRONMENTAL

Ambient Operating Temperature	-5°C to +40°C (not to exceed an average of more than 35°C in any 24 hours period)
Degree of Protection	Ordinary

MATERIAL

Material (Enclosure)	Polycarbonate
Metal Component Material	Brass

SIZE AND WEIGHT

Dimension (Height x Width x Depth)	77mm x 77mm x 38mm
Weight	Estimated 110 grams
Fixing Center	60mm

Recommended Flush Boxes	'ABB', 'Jung' Moulded Type and Steel Type Depth: min. 35mm Flush Boxes shall be complied to BS 4662
-------------------------	---

Compliance	BS 5733:1995 PSB test mark
------------	-------------------------------

Guarantee	3 years subject to Eubiq Limited Warranty Statement
-----------	---



www.eubiq.com

EUBIQ PRIVATE LIMITED. 9 JOO KOON CRESCENT SINGAPORE 629025
ALL RIGHTS RESERVED. EUBIQ AND GSS ARE REGISTERED TRADEMARKS OF EUBIQ PTE LTD.

DISCLAIMER: EUBIQ PRIVATE LIMITED RESERVES THE RIGHT TO ALTER ANY DETAILS OF SPECIFICATIONS OR EQUIPMENT WITHOUT PRIOR NOTICE. DETAILS OF SPECIFICATIONS AND EQUIPMENT ARE ALSO SUBJECT TO CHANGES TO SUIT LOCAL STANDARDS, CONDITIONS AND REQUIREMENTS. PLEASE CONSULT YOUR LOCAL DEALER FOR MORE INFORMATION OR LOGON TO EUBIQ WEBSITE.